

ATTACHMENTS

Equipped with additional tools, a Brokk becomes even more profitable for your business. Grapples, scabblers, buckets, drills and other devices greatly expand the machine's efficiency and versatility. Here's our wide and ever-expanding range of original Brokk attachments:



SB302



## ■ BREAKERS

	Hitting power*	Blows/min	Weight	Made for
<b>SB 52</b>	101 J/Nm	960 – 1 700	55 kg/121 lbs	Brokk 60
<b>SB 152</b>	254 J/Nm	840 – 1 900	140 kg/309 lbs	Brokk 100, 120D, 160
<b>SB 202</b>	406 J/Nm	850 – 1 800	200 kg/441 lbs	Brokk 160
<b>SB 302</b>	610 J/Nm	600 – 1 400	310 kg/683 lbs	Brokk 280
<b>SB 452</b>	855 J/Nm	550 – 1 250	441 kg/972 lbs	Brokk 400, 800
<b>SB 552</b>	1 048 J/Nm	650 – 1 150	520 kg/1 146 lbs	Brokk 400
<b>MB 1200</b>	2 709 J/Nm	340 – 680	1 200 kg/2 646 lbs	Brokk 800

\*Actual output, impact energy class (Joule/Nm)

A variety of chisels and tools can be fitted to the breakers. Other breaker brands can also be used on Brokk machines. Contact your local Brokk dealer or Brokk AB for information.

PTA-09



## ■ SIDE ANGLING DEVICE\*\*

	Angle	Weight*	Made for
<b>PTA-04,5</b>	±60°	140 kg/309 lbs	SB 102/Brokk 100, 120D
<b>PTA-06</b>	±70°	215 kg/474 lbs	SB 152/Brokk 160
<b>PTA-07</b>	±70°	330 kg/728 lbs	SB 202/Brokk 280
<b>PTA-09</b>	±55°	555 kg/1 224 lbs	SB 302/Brokk 400

\*With breaker

\*\* Requires one extra hydraulic function



## CONCRETE CRUSHERS\*\*



CC520

	Jaw opening	Rebars	Crushing force	Weight	Made for
<b>CC260</b>	250 mm/9.8 in	Ø16 mm/0.6 in	220 kN/22 t/ 49 Klbf	82 kg/ 181 lbs	Brokk 60
<b>CC340</b>	343 mm/14 in	Ø30 mm/1.2 in	360 kN /37 t/ 81 Klbf	160 kg/ 353 lbs	Brokk 100, 120D
<b>CC430*</b>	431 mm/17 in	Ø30 mm/1.2 in	382 kN/39 t/ 86 Klbf	265 kg/ 584 lbs	Brokk 160
<b>CC520*</b>	540 mm/21 in	Ø30 mm/1.2 in	466 kN/48 t/ 105 Klbf	407 kg/ 897 lbs	Brokk 280
<b>CC700*</b>	650 mm/26 in	Ø30 mm/1.2 in	680 kN/69 t/ 153 Klbf	610 kg/ 1 345 lbs	Brokk 400, 800

\*Option pulverizing pads

\*\*Free rotation



## METAL SHEARS\*



BMS 250-H

	Cutting force	Jaw opening	Weight	Made for
<b>HCS6</b>	214 kN/22 t/48 Klbf	267 mm/10.5 in	56 kg/123 lbs	Brokk 60, 100, 120D
<b>HCS7</b>	312 kN/32 t/70 Klbf	357 mm/14.1 in	158 kg/348 lbs	Brokk 100, 120D, 160
<b>CC420S</b>	740 kN/75 t/166 Klbf	145 mm/6 in	300 kg/661 lbs	Brokk 160, 280
<b>CC700S</b>	1 840 kN/188 t/414 Klbf	268 mm/11 in	695 kg/1 532 lbs	Brokk 400, 800
<b>BMS 100</b>	647 kN/66 t/145 Klbf	195 mm/7.7 in	380 kg/838 lbs	Brokk 160, 280
<b>BMS 140</b>	863 kN/88 t/194 Klbf	290 mm/11.4 in	645 kg/1 422 lbs	Brokk 400
<b>BMS 250-H</b>	1 353 kN/138 t/304 Klbf	375 mm/14.8 in	1 360 kg/2 998 lbs	Brokk 800
<b>MC 200</b>	490 kN/50 t/110 Klbf	200 mm/7.9 in	120 kg/265 lbs	Brokk 100, 160, 120D
<b>TC 120</b>	662 kN/68 t/149 Klbf	120 mm/5 in	305 kg/672 lbs	Brokk 160, 280

\*Requires one extra hydraulic function  
Rotator with continuous rotation



## BUCKETS\*

2501



Volume	Width	Weight	Made for
20 l/0.7 cu ft	330 mm/13 in	20 kg/44 lbs	Brokk 60
60 l/2.1 cu ft	520 mm/20.5 in	61 kg/134 lbs	Brokk 100, 120D
80 l/2.8 cu ft	690 mm/27.2 in	76 kg/168 lbs	Brokk 160
250 l/8.8 cu ft	930 mm/36.6 in	195 kg/430 lbs	Brokk 280, 400, 800
700 l/24.7 cu ft	1 050 mm/41.3 in	650 kg/1 433 lbs	Brokk 800

\*See load diagram for each Brokk machine




C05HPX



## CLAMSHELL BUCKETS\*

	Volume	Opening range	Width	Weight	Made for
<b>C02H-25</b>	25 l/0.9 cu ft	725 mm/28.5 in	250 mm/9.8 in	110 kg/243 lbs	Brokk 100, 120D
<b>C03H-35</b>	65 l/2.3 cu ft	880 mm/34.6 in	350 mm/13.8 in	175 kg/386 lbs	Brokk 160
<b>C05H-40</b>	115 l/4.1 cu ft	1 090 mm/42.9 in	400 mm/15.7 in	210 kg/463 lbs	Brokk 280
<b>C05HPX-60</b>	170 l/6.0 cu ft	1 110 mm/43.7 in	600 mm/23.6 in	375 kg/827 lbs	Brokk 400
<b>C08HPX-80</b>	300 l/10.6 cu ft	1 250 mm/49.2 in	800 mm/31.5 in	580 kg/1 279 lbs	Brokk 800

\*See load diagram for each Brokk machine  
Rotator with continuous rotation  
Requires one extra hydraulic function



## MULTI PURPOSE GRAPPLES\*



A05HPX-40

	Volume	Opening range	Width	Weight	Made for
<b>A02H-30</b>	35 l/1.2 cu ft	835 mm/32.9 in	300 mm/11.8 in	152 kg/335 lbs	Brokk 100, 120D, 160
<b>A03H-40</b>	70 l/2.5 cu ft	1 475 mm/58.1 in	390 mm/15.4 in	285 kg/628 lbs	Brokk 280
<b>A05HPX-40</b>	100 l/3.5 cu ft	1 400 mm/55.1 in	400 mm/15.7 in	410 kg/904 lbs	Brokk 400
<b>A09HPX-50</b>	200 l/7.1 cu ft	1 650 mm/65 in	500 mm/19.7 in	675 kg/1 488 lbs	Brokk 800

### Orange Peel Grapple



KM651-4

<b>KM651-4 180</b>	180 l/6.4 cu ft	1 450 mm/57.1 in	1 070 mm/42.1 in	520 kg/1 146 lbs	Brokk 400
<b>KM651-4 250</b>	250 l/8.8 cu ft	1 550 mm/61 in	1 285 mm/50.6 in	870 kg/1 918 lbs	Brokk 800

\*See load diagram for each Brokk machine  
Requires one extra hydraulic function  
Rotator with continuous rotation

G30



## SORTING & DEMOLITION GRAPPLES\*

	Jaw opening	Weight	Made for
<b>G30</b>	300 mm/11.8 in	42 kg/93 lbs	Brokk 60
<b>G50</b>	400 mm/15.7 in	140 kg/309 lbs	Brokk 100, 120D, 160
<b>D02H-30</b>	790 mm/31.1 in	133 kg/293 lbs	Brokk 100, 120D, 160
<b>D03HPX-40</b>	975 mm/38.4 in	310 kg/683 lbs	Brokk 280
<b>D05HPX-50</b>	1 135 mm/44.7 in	400 kg/882 lbs	Brokk 400
<b>D09HPX-60</b>	1 400 mm/55.1 in	595 kg/1 312 lbs	Brokk 800

\*See load diagram for each Brokk machine  
Requires one extra hydraulic function  
Rotator with continuous rotation



D02H

ER 100



## SCABLERS

	Cutting depth**	Width	Weight	Made for
<b>RT 15-40</b>	0-5 mm/0-0.2 in	120 mm/4.7 in	66 kg/146 lbs	Brokk 60
<b>RT 15-90*</b>	0-5 mm/0-0.2 in	203 mm/8 in	102 kg/225 lbs	Brokk 100, 120D, 160
<b>ER 50****</b>	0-30 mm/0-1.2 in	480 mm/18.9 in	160 kg/353 lbs	Brokk 100, 120D, 160
<b>ER 100****</b>	0-65 mm/0-2.6 in	610 mm/24 in	345 kg/761 lbs	Brokk 160, 280, 400, 800
<b>ER 250****</b>	0-80 mm/0-3.1 in	680 mm/26.8 in	545 kg/1 202 lbs	Brokk 400***

\*Cover and suction on request

\*\*Data depending on concrete quality

\*\*\*B800 on request depending on requirement

\*\*\*\*Requires drainage hose

BCP250



## PLANERS

	Cutting depth	Width	Weight	Made for
<b>BCP 215* **</b>	0-5 mm/0-0.2 in	215 mm/8.5 in	230 kg/507 lbs	Brokk 100, 120D
<b>BCP 250* **</b>	0-5 mm/0-0.2 in	265 mm/10.4 in	345 kg/761 lbs	Brokk 160
<b>BCP 350* **</b>	0-5 mm/0-0.2 in	335 mm/13.2 in	600 kg/1 323 lbs	Brokk 280, 400
<b>PLB 300*</b>	0-50 mm/0-2 in	300 mm/11.8 in	452 kg/996 lbs	Brokk 280, 400

\*Available with cover and suction

\*\*Requires extra hydraulic function, drainage hose, cable kit, counter weight in some occasions

Requires load holding. On request

PLB 300



TE 160-100



## DRILLING EQUIPMENT\*\*\*

	Length	Drill diameters	Drill steel size	Max. stroke length**	Weight	Made for
<b>TE 160-100</b>	1 910 mm/ 75.2 in	33 – 42mm 1.3 – 1.7 in	R25	1 000 mm/ 3.3 ft	225 kg/ 496 lbs	Brokk 100, 120D, 160
<b>TE 260-180*</b>	2 900 mm/ 114.2 in	33 – 52 mm 1.3 – 2 in	R32	1 830 mm/ 6 ft	415 kg/ 915 lbs	Brokk 160, 280, 400
<b>TE 260-240*</b>	3 500 mm/ 137.8 in	33 – 52 mm 1.3 – 2 in	R32	2 435 mm/ 8 ft	432 kg/ 952 lbs	Brokk 280, 400
<b>TE 360-240*</b>	3 590 mm/ 141.3 in	42 – 76 mm 1.7 – 3 in	R32	2 435 mm/ 8 ft	644 kg/ 1 420 lbs	Brokk 400, 800

\*Extension rod drilling

\*\*Per stroke with open centerizer

\*\*\*Requires drainage hose, cable kit, counter weight in some occasions, water or airflushing

Brokk Beam Grapple



## ■ BEAM GRAPPLE\*

	Jaw opening	Beam weight	Weight	Made for
<b>Brokk Beam Grapple</b>	250 mm/9.8 in	B280: 90 kg/198 lbs B400: 500kg/1 102 lbs B800: 500 kg/1 102 lbs	320 kg/705 lbs	Brokk 280, 400, 800

\*Requires load holding valves with hose burst function  
Requires two extra hydraulic functions

Brokk Shot Crete



## ■ SHOT CRETE\*

	Concrete hose (di)	Gunning pressure	Air pressure	Weight	Made for**
<b>Brokk Shot Crete</b>	45 mm/1.8 in	Depend on concrete pump	Depend on concrete pump	180 kg/397 lbs	Brokk 280, 400, 800

\*Requires two extra hydraulic functions  
\*\*Other models on request

BCS10



## ■ CUT OFF SAW\*

	Saw disk diameter**	Cutting depth***	Weight	Made for
<b>BCS 8</b>	400 mm/16 in	170 mm/7 in	62 kg/137 lbs	Brokk 60
<b>BCS 10</b>	400 mm/16 in	170 mm/7 in	65 kg/143 lbs	Brokk 100, 120D, 160
<b>BCS 25****</b>	800 mm/31 in	260 mm/10 in	192 kg/423 lbs	Brokk 160
<b>BCS 35****</b>	800 mm/31 in	260 mm/10 in	195 kg/430 lbs	Brokk 280, 400, 800

\*Requires one extra hydraulic function  
\*\*Different saw disks available depending on material  
\*\*\*With new saw disk  
\*\*\*\*Requires drainage hose



C20



## ■ SPLITTERS

	Length****	Drill hole diameter	Splitting force theoretical	Total weight*****	Made for
<b>C20 V**</b>	1 833 mm/72 in	76 mm/3 in	14 760 kN-17 660 kN/ 1 500 t-1 800 t	455 kg/ 1 003 lbs	Brokk 280*- 400
<b>C20 H***</b>	1 790 mm/70 in	76 mm/3 in	14 760 kN-17 660 kN/ 1 500 t-1 800 t	460 kg/ 1 014 lbs	Brokk 280*- 400
<b>C20 J**</b>	2 110 mm/83 in	76 mm/3 in	14 760 kN-17 660 kN/ 1 500 t-1 800 t	440 kg/ 970 lbs	Brokk 280*- 400

\*Require counter weight  
\*\*Requires one extra hydraulic function  
\*\*\*Requires two extra hydraulic functions  
\*\*\*\*Value without wedge set. Value without mounting kit  
\*\*\*\*\*With mounting kit and wedge set